

REPAIR-ALL POWERKIT 6X5GR MINI MOD. CLAY

€ 11,95

Excl. BTW: € 9,88

Afbeeldingen



Beschrijving

Application

- Fast curing epoxy putty for repairing, bonding, assembling, sealing and filling
- Suitable for hard material: Stone, concrete, metal, wood, ceramic, porcelain and many plastics

Features

- Grinding, drilling, sawing and painting possible after curing
- Easy to apply, see "Processing"
- Fast curing: 5-10 minutes
- Can be used internally and externally
- Water resistant: Suitable for continuous water exposure
- Cures under water
- Chemical resistance to hydrocarbons, ketones, alcohol, esters, salt solutions, diluted acids and bases
- Including storage box
- **3-46720**: 6 portions of 5g each

Technical Specifications

Appearance:	Two-component adhesive in putty
Chemical Base:	Aliphatic polyfunctional epoxy resin (MG > 700)
Consistency:	Solid
Solid matter:	approx. >99 %
Density:	approx. 2 g/cm ³
Water Resistance:	Very good
Filling Capacity:	Very good

Processing

The repair or adhesive surfaces must be free of dust and grease. Roughen smooth surfaces. Cut off the required amount and knead until the colour is uniform. The more uniform the mixing of the two components, the stronger the hardened material. Apply the kneading mass to the surface and press it firmly or press it into gaps and holes. The working time is 4 minutes, at room temperature after 10 minutes solid.

Productinformatie

Artikelnummer	POWERKIT
Merk	UHU
Is on Sale	Nee

