


RELAIS 1 X MAAK 12VDC 40A 90 OHM

€ 4,95

Excl. BTW: € 4,09

Afbeeldingen



Beschrijving

Features

- 40A contact rating
- High operating temperature 125°C
- Quick connect terminals
- Plastic dust cover with plastic mounting breacket
- ISO/TS 16949, ISO14001

Technical Specifications

Contact:	
Contact Material:	AgSnO ₂
Rated Current:	40A
Max. Switching Voltage:	28V DC
Max. Switching Power:	560W
Operate/Release Time:	7/5ms
Testing Voltage (FCC)	

Coil/Contact:	750V _{RMS}
Open Contacts:	500V _{RMS}
Lifetime	
Mechanical, Min.:	1x10 ⁷ Operations
Electrical, Min. (40A / 14V DC)	1x10 ⁵ Operations
Operating Temperature:	-40...+125°C
Weight Approx.:	36g

Coil Data

Part Nr	U _N	U _{min.}	U _{max.}	P _N	R _N
	[V DC]	[V DC]	[V DC]	[mW]	[Ohm]
R012D1MS	12	7,8	15,6	1600	90

U_N = Rated Voltage, U_{Min.} = Minimum Operating Voltage, U_{Max.} = Maximum Operating Voltage, P_N = Rated Power, R_N = Coil Resistance; Rated Value ±10%; All Specifications Measured at 20°C

Productinformatie

Artikelnummer	R012D1MS
Merk	ZETTLER
Is on Sale	Nee

