

RELAIS 24VDC 3 X MAAK/3 X BREEK 8A

€ 29,95

Excl. BTW: € 24,75

Afbeeldingen



Beschrijving

Features

- Relay with forcibly guided contacts according to EN50205
- 6-pole safety relay
- Category of protection RTIII (wash tight)

Application

Emergency shut-off, press control, safety modules, elevator and escalator control

Technical Specifications

Contact	
RO24D4M2B:	4xNO+2xNC
RO24D5M1B:	5xNO+1xNC
RO24D3M3B:	3xNO+3xNC
Contact Material:	AgSnO ₂
Rated Current:	8A
Max. Switching Voltage:	400V AC
Max. Switching Power:	2000VA
Creepage/Clearance:	5,5/5,5mm
Testing Voltage	
Coil/Contact:	3000V _{rms}
Contact/Contact:	3000V _{rms}
Opening Contact:	1500V _{rms}
Lifetime	
Mechanical:	10x10 ⁶ Operations
Operating Temperature:	-25...+70°C
Weight Approx.:	30g

Coil Data

Part Nr.	U_N [V DC]	U_{An} [V]	U_{Ab} [V]	P_N mW	R_N Ohm
RO24D4M2B	24	18	2,4	1200	480
RO24D5M1B	24	18	2,4	1200	480
RO24D3M3B	24	18	2,4	1200	480

U_N = Rated Voltage, U_{An} = Operate Voltage, U_{Ab} = Release Voltage, P_N = Rated Power, R_N = Coil Resistance; All Specifications Measured at 23°C

Productinformatie

Artikelnummer	RO24D3M3B
Merk	TE CONNECTIVITY
Is on Sale	Nee

