

LI-ION BATTERIJ LADER 29,4V/2A/58,8W MET DC 2.1X5.5MM PLUG

€ 89,95

Excl. BTW: € 74,34

Afbeeldingen



Beschrijving

Features

- 3-Stage charge control with current detection as charge termination
- Universal input
- 3-Colour LED displays
- Mains connection cable with Euro plug and C7 small appliance socket can be ordered
- Exchangeable DC connectors (must be ordered separately)
- Protected against short circuit and reverse polarity
- Protection class II
- For applications in medical technology
- Safety standards: EN60335-2-29, EN 60601-1, EN 60950
- EMC standards: EN55014-1 and others
-

Technical Specifications

Input Voltage Range:	90...264V AC
	47...63Hz
Operating temperature range:	-25...+40°C
Storage temperature range:	-25...+85°C
Ripple:	<100mV _{pp}
Withstand Voltage (I/P-O/P):	4000V AC/5700V DC
Cable length:	1,80m
Dimensions:	135x80x44 mm
Weight:	390g
Protection class:	IP 41

I/P = Input, O/P = Output

Part Nr.	Cells	U _A	I _L	P _A	h
		[V]	[A]	[W]	[%]
MA2440135000	3	12,6	4	51	>81
MA2440165000	4	16,8	3,5	59	>85
MA2440295000	7	29,4	2,5	74	>85
MA2440425000	10	42	2,4	76	88
MA2440505000	12	50,4	1,2	73	87
MA2440595000	14	58,8	1	76	88

U_A= Charging Voltage, I_L= Charging Current, Max. , P_A= Output Power, h = Efficiency

Productinformatie

Artikelnummer	MA2440295
Merk	MASCOT
Is on Sale	Nee

