


GESCHAKELDE VOEDING SINGLE OUTPUT 1200W 5V/240A

€ 499,00

Excl. BTW: € 412,40

Afbeeldingen



Beschrijving

Features

- Enclosed case, built-in fan, screw terminals
- Universal input
- Overload protection, current limiting, hiccup after 5s
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- Low profile
- Parallel function
- Active current sharing up to 6000W (3+1 units)
- Built-in remote On/Off control
- Power fail signal
- Built-in remote sense function
- Built-in auxiliary power 12V/0,1A
- EMC: Conducted Emission EN55032/EN55011 Class B, Radiated Emission EN55032/EN55011 Class A

Technical Specifications

Input Voltage:	90...264V AC (47...63Hz)
	127...370V DC
Input Inrush Current, Max.:	60A
Leakage Current, Max.:	2mA
Output Voltage Adjustment:	±10%
Over Load Protection:	105...135%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-20...+70°C
Weight:	3000g

I/P = Input, O/P = Output, FG = Frame Ground

Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
RSP-1500-5	5	0...240	1200	2	150	80
RSP-1500-12	12	0...125	1500	1	150	87
RSP-1500-15	15	0...100	1500	1	150	87
RSP-1500-24	24	0...63	1512	1	150	90
RSP-1500-27	27	0...56	1512	1	150	90
RSP-1500-48	48	0...32	1536	1	200	91

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

Artikelnummer	RSP150005
Merk	MEANWELL
Is on Sale	Nee

