


## DIN-RAIL VOEDING 105MM 150W 24V/6,25A

€ 47,95

Excl. BTW: € 39,63

### Afbeeldingen



### Beschrijving

#### Features

- Direct assembly on DIN Rail
- Enclosed case, Touch-guard screw terminals
- Universal input
- Overload protection, current limiting, auto recovery
- Protections: short circuit, over load, over voltage
- Low no load power consumption
- Power-on LED display
- Insulation Class II



#### Technical Specifications



Input Voltage:

85...264V AC (47...63Hz)

120...370V DC

|                             |             |
|-----------------------------|-------------|
| Input Inrush Current, Max.: | 70A         |
| Over Load Protection:       | 105...135%  |
| Withstand Voltage, I/P-O/P: | 4000V AC    |
| Operating Temperature:      | -30...+70°C |
| Weight:                     | 310g        |

I/P = Input, O/P = Output



| Part Nr. | $U_A$ | $I_A$ | $P_A$ | $DU_A$ | $U_{RN}$             | h    |
|----------|-------|-------|-------|--------|----------------------|------|
|          | [V]   | [A]   | [W]   | [%]    | [mV <sub>p-p</sub> ] | [%]  |
| HDR10012 | 12    | 11,3  | 135,6 | 2      | 120                  | 89   |
| HDR10015 | 15    | 9,5   | 142,5 | 1      | 120                  | 89,5 |
| HDR10024 | 24    | 6,25  | 150   | 1      | 150                  | 90,5 |
| HDR1048  | 48    | 3,2   | 153,6 | 1      | 240                  | 90,5 |

$U_A$  = Output Voltage,  $I_A$  = Output Current,  $P_A$  = Output Power,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise, h = Efficiency

## Productinformatie

|               |          |
|---------------|----------|
| Artikelnummer | HDR15024 |
| Merk          | MEANWELL |
| Is on Sale    | Nee      |

