

INFRAROOD LICHTSLUIS TOT 100M DUAL BEAM 12V-24VDC IP65

€ 79,94

Excl. BTW: € 66,07

Afbeeldingen



Model	AX-602	AX-1002
Warning distance	(outdoor) 60m	100m
	(indoor) 180m	300m
Number of beams	2 beams simultaneously	
Detection method	interrupted detection type	
Light source	Infrared digital pulse type	
Shading time	50-240ms (stepless adjustable)	
Power supply voltage	DC12V-24V	
Beam signal threshold	±0.5%	
Alarm output	Relay contact output NO, NC	
Condensation and frost countermeasures	Heating housing (optional)	
Current consumption	≤100mA (at 24V)	
Working temperature	-25°C ~ 55°C	
Working humidity	5% ~ 95%RH (relative humidity)	
Optical axis adjustment angle (horizontal)	180° (±50°)	
Optical axis adjustment angle (vertical)	20° (±10°)	
Material	PC	

Beschrijving

Product Features:

- 1. Dual-beam Infrared Sensor:** Adopts aspherical coated optical lenses and professional DSP chip, strong anti-interference, high levels of anti-RFI / EMI capability.
- 2. Digital Fuzzy Artificial Intelligence Recognition:** Intelligent power emission.

3. **Intelligent 8 Frequency Conversion:** Anti-interference and anti-false alarms.

4. **Digital Display:** Shows the bus address, signal strength and operating frequency in real time.

5. **Adjustable Optical Axis Angle:** 90°left/right, 10°up/down for easy installation.

6. **Tamper Function:** This product has a tamper switch, which can trigger an alarm when the outer cover is loose under working conditions.

Productinformatie

Artikelnummer	PEM45DB
Merk	Brand
Is on Sale	Nee

