

DIN-RAIL VOEDING 32MM 75W 12V/6,3A

€ 34,94

Excl. BTW: € 28,88

Afbeeldingen



Beschrijving

Features

- Direct assembly on DIN Rail
- Enclosed case, Touch-guard screw terminals
- Universal input
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- DC OK LED display

Technical Specifications

| | |
|-----------------------------|--------------------------|
| Input Voltage: | 90...264V AC (47...63Hz) |
| | 127...370V DC |
| Input Inrush Current, Typ.: | 35A |

| | |
|----------------------------|-------------|
| Leakage Current, Max.: | 1mA |
| Output Voltage Adjustment: | +12% |
| Over Load Protection: | 105...130% |
| Withstand Voltage | |
| I/P-O/P: | 3000V AC |
| I/P-FG: | 2000V AC |
| O/P-FG: | 500V AC |
| Operating Temperature: | -20...+70°C |
| Weight: | 510g |

I/P = Input, O/P = Output, FG = Frame Ground

| Part Nr. | U_A | I_A | P_A | DU_A | U_{RN} | h |
|------------------|-------|---------|-------|--------|----------------------|------|
| | [V] | [A] | [W] | [%] | [mV _{p-p}] | [%] |
| NDR-75-12 | 12 | 0...6,3 | 75,6 | 2 | 80 | 85,5 |
| NDR-75-24 | 24 | 0...3,2 | 76,8 | 1 | 120 | 88 |
| NDR-75-48 | 48 | 0...1,6 | 76,8 | 1 | 150 | 89 |

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

| | |
|---------------|----------|
| Artikelnummer | NDR7512 |
| Merk | MEANWELL |
| Is on Sale | Nee |

