

ANTENNE BASIS 27MHZ 5/8 3.65DBI

€ 239,94

Excl. BTW: € 198,30

Afbeeldingen



Beschrijving

Grazioli FE10V is a $5/8 \lambda$ antenna for the 10 or 11m band. Extremely robust, performing antenna with a low angle of radiation, and that could withstand extremely high powers (5kW CW continuous all-mode). The result is FE10V which has

unique characteristics in the current market and collects all our experience in this field.

The coil plays a fundamental role for impedance matching and maximum RF transfer, its shape given by the length / diameter ratio, the pitch between turns, the material and diameter of the wire and the presence or absence of metal cores within it, determine the quality factor. The coil is directly connected to ground in direct current (DC-Ground), in this way atmospheric disturbances and background noises are significantly reduced.

For our tubes we have used the best alloy that can be used for the construction of the antennas the AW6063-T66 alloy of Aluminum, Magnesium and Silicon hardened to the T-66 state which gives the whip an exceptional resistance, which is made by extrusion and subsequently cold drawn. The "Ground Plane" is composed of 4 robust radials with a length of 2.7m

The FE10V connector is not a commercial SO-239 type connector as most manufacturers use. The connector was designed and built directly by us, has a real impedance of 50 Ohms and can be used up to 500 MHz. The goal was to create a reliable connector capable of withstanding 5kW CW continuous at 30 MHz. The body is made of CW614N nickel-plated brass, while the pin is plated in 24K gold to avoid oxidation and equipped with a 4-fin insulator that maintains its centering and elasticity, avoiding contact losses. The insulating part is made of PTFE which is one of the best insulating materials.

The fixing bracket is made of 2.5mm thick AISI304 stainless steel, it is fixed to the antenna tube by means of a clamp closure system, creating an extremely strong mechanical locking. Fixing to the mast is made with AISI304 M6 V-Bolt and high type nuts to facilitate tightening

Electrical data

- Electrical type: $5/8 \lambda$ center feed
- Gain: 1.50 dBd - 3.65 dBi
- VSWR: $\leq 1.2:1$
- Bandwidth: ≥ 1.4 MHz at 26MHz / ≥ 1.6 MHz at 30 MHz
- Maximum continuous power: 5000 Watts (CW)
- Impedance: 50 Ohm
- Polarization: Linear vertical

Mechanical data

- Materials: Aluminum Alloy AW6063-T66 hard drawn tube, Fiberglass, Brass, PTFE. All hardware are made of SS AISI-304 and 316
- Mast Ø: 40 - 54 mm
- Max wind resistance: 130 km/h
- Height: 7630 mm (including bracket)
- Weight: 6000 gram
- Mounting type: On mast
- Antenna connector: UHF-female, PTFE insulator & gold plated central pin
- Radial length: 2700 mm

Artikelnummer	FE10V
Merk	GRAZIOLI
Is on Sale	Nee

