

PRESIDENT BARRY II ASC AM/FM

€ 119,95

Excl. BTW: € 99,13

Afbeeldingen





Beschrijving

De Barry II AM/FM is de opvolger van de Barry en beschikt nu over USB-ingang en een VOX-functie. Deze dubbelspanning (12/24V) CB is President's basismodel radio met een groot helder display en werkt op alle Europese banden.

Frequentiebereik: 26,965 - 27,405 MHz

Features

- Modulation: AM / FM
- Multi-bands: Yes
- Output power: 4 Watt
- Channels: 40 AM / FM
- Display type: LCD display
- Display colors: Green / Orange / Purple / Blue / Cyan / Yellow / Clear Blue

- VOX Function: Yes
- USB: Yes
- Noise blanker: Yes
- Squelch: ASQ (Automatig Squelch Systeem) / Manual squelch /
- Emergency channel: Yes
- External speaker socket: Yes
- External PA socket: Yes
- S-meter: Yes
- TOT (time out timer): Yes
- External VOX socket: Yes
- Roger Beep: Yes

Electrical data

- Voltage: 13,8 Volt / 24 Volt /

Transmitter

- Audio frequency response: 300 Hz - 3 kHz
- Microphone sensitivity: 7 mV
- Frequency allowance: \pm 200 Hz
- Transmission interference: inferior to 4 nW (- 54 dBm)
- Emitted power in the adjacent channel: inferior a 20 μ W
- Modulated signal distortion: 2 %
- Drain: 13.2 Volt: 1.7 A / 26.4 Volt: 0.85 A

Receiver

- AM sensitivity: 0,5 μ V - 113 dBm
- FM sensitivity: 0,35 μ V - 116 dBm
- Frequency response: 300 Hz - 3 kHz
- Adjacent channel selectivity: 60 dB
- Maximum audio power: 2.5 Watt
- Squelch sensitivity: min. 0.2 μ V - 120 dBm / max. 1 mV - 47 dBm
- Frequency image rejection rate: 60 dB
- Intermediate image rejection rate: 70 dB
- Drain: 13.2 Volt: 160 - 420 mA / 26.4 Volt: 100 - 250 mA

Mechanical data

- Length: 180 mm
- Height: 45 mm
- Width: 125 mm
- Weight: 900 gram
- Antenna connector: UHF (PL) female (SO-239)
- Mike connector: 6 pin connector

Inside the box

- Transceiver: 1 pcs
- Microphone: 1 pcs
- Fixing screws: 1 set
- Mounting bracket: 1 pcs

- Power lead: 1 pcs
- User Manual: English, Spanish, French, Polish

Productinformatie

Artikelnummer	BARRYII
Merk	PRESIDENT
Is on Sale	Nee

