

STABO XM 3004E-R VOX

€ 344,95

Excl. BTW: € 285,08

Afbeeldingen



Beschrijving

De Stabo XM 3004E-R VOX is een mobiel CB-radioapparaat en kan worden gebruikt op 12 en 24 Volt. De XM 3004E beschikt over een instelbare VOX-functie (5 niveaus) die het mogelijk maakt om handsfree te communiceren met de

optionele Stabo VOX-microfoon. Bij deze versie wordt een originele din houder van Stabo meegeleverd.

Frequentiebereik: 26,965 - 27,405 MHz

Features

- Modulation: AM / FM
- Multi-bands: Yes
- Output power: 4 Watt
- Channels: 40 AM / FM
- Display type: LCD display
- Display colors: Green / Orange / Purple / Blue / Cyaan / Yellow / Clear Blue
- VOX Function: Yes
- Noise blanker: Yes
- Squelch: ASQ (Automatig Squelch Systeem) / Manual squelch /
- Emergency channel: Yes
- Scan function: Yes
- Quick channel selection: Yes
- External speaker socket: Yes
- TOT (time out timer): Yes
- Din mount: Yes
- External VOX socket: Yes
- Roger Beep: Yes

Electrical data

- Voltage: 13,8 Volt / 24 Volt /
- Operating temperature: -10° to +55° C

Transmitter

- Audio frequency response: 300 Hz - 3 kHz
- Microphone sensitivity: <3 mV
- Frequency allowance: ± 600 Hz
- Drain: 13.2 Volt: 2 A max / 24 Volt: 2 A max

Receiver

- AM sensitivity: ≤ -107 dBm 20 dB SINAD
- FM sensitivity: ≤ -107 dBm 20 dB SINAD
- Frequency response: 300 Hz - 3 kHz
- Adjacent channel selectivity: 60 dB
- Maximum audio power: 2 Watt
- Internal speaker: 8 Ohm
- Squelch sensitivity: min. 0.2 µV
- Image rejection: 70 dB
- Drain: 300 mA nominal / 750 mA max.

Mechanical data

- Length: 165 mm
- Height: 35 mm (without DIN-mount)
- Width: 115 mm (without DIN-mount)

- Weight: 600 gram (without DIN-mount)
- Antenna connector: UHF (PL) female (SO-239)
- Mike connector: 6 pin connector

Inside the box

- Transceiver: 1 pcs
- Microphone: 1 pcs
- Fixing screws: 1 set
- Power lead: 1 pcs
- DIN mount: 1 pcs
- User manual: English, German, French, Polish,

Productinformatie

Artikelnummer	XM3004ER
Merk	STABO
Is on Sale	Nee

