

DC MAXI JOLLY HC LED DRIVER 26-44VDC 1050-2010MA 55W 110X76X30MM DIMBAAR 1-10V & PUSH

€ 49,95 Excl. BTW: € 41,28

Afbeeldingen



Beschrijving





Direct current dimmable electronic drivers multicurrent for power LED and LED modules

Driver for built-in use.

Multi-power driver supplied with dip-switch for the selection of the output current.

Active Power Factor Corrector.

Light regulation 0-100% by means of PUSH function (mains voltage):

- a short push to turn on and off;
- a longer push to increase or decrease light intensity;
- regulation automatically stops at minimum and maximum values;
- for another on, regulation or off command, release the push button and give the desired command again.

Maximum length of the cable, from push button to last driver, must be max. 15 m.

In case of applications where the cable is longer than 15 m, keep this separate from the 240 V mains cable.

Possibility to use PUSH function to 4/5 drivers without sync cable.

Synchronization cable supplied separately.

Max. 10 drivers synchronization, is possible command only one driver (1Master + 9Slaves).

ATTENTION: only use normally open push

buttons with no incorporated warning light.

Light regulation O-100% by means of PUSH function or Interface 1...10 V (1...10 Vdc source with double or reinforced insulation with respect to AC mains). For regulations see page 104-105.

Current regulation $\pm 5\%$ including temperature variations.

It can be used for lighting equipment in protection class I and II.

Input and output terminal blocks on the same side (terminal area 2,5 mm2).

Driver can be secured with slot for screws.

Protections:

- against overheating and short circuits;
- against mains voltage spikes;
- against overloads.

Thermal protection = C.5.a.

Can be switched on and off on secondary circuit for power LED.

Auxiliary output 12 V max. 100 mA.

Analogical input for thermal sensor connection.

Productinformatie

Artikelnummer	122415
Merk	TCI
Is on Sale	Nee

