

ALINCO DM-30G VOEDING 9-15VDC

€ 119,95

Excl. BTW: € 99,13

Afbeeldingen



Beschrijving

Deze betaalbare schakelende voeding bevat veel functies in een ultracompact, lichtgewicht ontwerp met een variabele uitgang van 9-15 V en een continue stroomsterkte van 20 A en een piek van 30 A.

Handig voor radiogebruikers: het Noise Offset Circuit verplaatst ongewenst schakelgeluid naar een andere frequentie. Andere kenmerken zijn onder meer een grote verlichte digitale volt-/ampèremeter, aansluitpunten op het achterpaneel (30 A piek/per paar), snelaansluitingen op het voorpaneel (5 A piek/per paar), Anderson-polen, spanningsaanpassing (9-15 V) of vast op 13,8 V, rimpel minder dan 80 mVp-p en drievoudige circuitbeveiliging voor kortsluiting, oververhitting en stroombeperking.

- Input voltage: 230 Volt
- Output voltage: 13.8 Volt
- Adjustable output voltage: 9-15 Volt
- Continuous load: 20A
- Peak load: 30A
- Ripple voltage: $\leq 80\text{mVp-p}$
- Fuse: 5A
- Display indicator: Voltage / ampère
- Background light: Yes
- Fan: Yes
- Short circuit protection: Yes
- Overload protection: Yes
- Cooling method: Forced air cooling

Mechanical data

- Length: 155 mm
- Height: 75 mm
- Width: 205 mm
- Weight: 1600 gram

Inside the box

- Power supply: Yes
- AC cord: Yes
- User manual: English

Productinformatie

| | |
|---------------|--------|
| Artikelnummer | DM30G |
| Merk | ALINCO |
| Is on Sale | Nee |

