

## GESCHAKELDE VOEDING 5.0V 0.80A 4W AANSLUITDRADEN

€ 15,95

Excl. BTW: € 13,18

### Afbeeldingen



### Beschrijving

RAC04NE-K are exceptionally robust AC/DC modules for a maximum power range of 4 to 6 watts and have been specially designed for continuous operation under significantly expanded operating conditions. The full output power of 100% is available from -40°C to 80°C and also for all global single-phase AC networks or 100/115/200/230/277 VAC. OVC III is maintained up to 3000m operating altitude, or overvoltage category OVC II up to 5000m. The immunity to interference voltages is 2 kV (L-N); 4 kV (L-PE), which is significantly higher than usual for modules of this size. An integrated emission filter offers scope for system integration in accordance with EN55032 "B", also with load-side potential equalization of sensitive electronics or protection type PELV. In addition to the encapsulated print modules, a wired mechanical variant with mounting tabs and IP65 water resistance is available, which has also been approved according to IEC61347.

| Attributes              | RAC04NE-05SK/277/W                                               |
|-------------------------|------------------------------------------------------------------|
| AC/DC or DC/DC          | AC/DC                                                            |
| Power (W)               | 4                                                                |
| Isolation               | Isolated                                                         |
| Vin (V)                 | 85 - 305                                                         |
| Main Vout (V)           | 5                                                                |
| Nr. of Outputs          | Single                                                           |
| Iout 1 (mA)             | 800                                                              |
| Isolation (kV)          | 4.2                                                              |
| Mounting Type           | Wired                                                            |
| Package Style           | Encapsulated 1.48"x0.97" (IP65)                                  |
| Length (mm)             | 37.8                                                             |
| Width (mm)              | 24.8                                                             |
| Height (mm)             | 18.7                                                             |
| Certifications          | CB, CE, EN 55032, EN 60335-1, EN 61347-1, EN 62368-1, UL 62368-1 |
| MIN Operating Temp (°C) | -40                                                              |
| MAX Operating Temp (°C) | 75                                                               |
| Protections             | OCP, OVP, SCP                                                    |
| Directives              | REACH, RoHS 2+ (10/10), WEEE                                     |

[Klik hier om de datasheet te bekijken](#)

### Productinformatie

|               |            |
|---------------|------------|
| Artikelnummer | RAC04NE05W |
| Merk          | RECOM      |
| Is on Sale    | Nee        |

