

## LED VOEDING 24V/2,5A 60,0W OPEN FRAME

€ 26,95

Excl. BTW: € 22,27

### Afbeeldingen



### Beschrijving

#### Features

- Universal input
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Open-frame
- Built-in active PFC function
- Suitable for LED lighting and moving sign applications

Input Voltage: 90...264V AC (47...63Hz)

Input Inrush Current, Max.: 42A

Over Load Protection: 100...115%

Withstand Voltage

(I/P-O/P): 3750V AC

(I/P-FG): 1880V AC

(O/P-FG): 500V AC  
I/P = Input, O/P = Output, FG = Frame Ground  
Operating Temperature: -30...+70°C  
Weight: 160g  
Dimensions 101,6x50,8x28mm (LxWXH)

Output Voltage: 24Vdc  
Output Current Range: 0 - 2,5A  
Current Adjustment: 1,875 - 2,5A  
Output Power: 60W  
Output Voltage Tolerance: 10%  
Ripple & Noise: 4,5Vp-p  
Typ. Efficiency: 88%

## Productinformatie

---

|               |          |
|---------------|----------|
| Artikelnummer | PLP6024  |
| Merk          | MEANWELL |
| Is on Sale    | Nee      |

