

BUTTON ROND MK/BRK 250V 2A GROEN

€ 12,50

Excl. BTW: € 10,33

Afbeeldingen



Beschrijving

General information

Colour of lens opaque green

Form of lens protruding lens

Form of collar round

Dimensions

Overall height 10.5 mm

Diameter of collar 22 mm

Mounting depth 34 mm

Mounting hole 18.2 mm

Electrical characteristics

Contact resistance acc. to life max. 200 mΩ

Rated voltage AC max. 250 V

Rated current max. 2 A

Mechanical characteristics

Robustness min. 100 N

Operating force max. 9.5 N

Operating travel 5 mm

Switching travel NO 3.7 mm

Switching travel NC ---

Mechanical design

Terminals screw terminals

Mounting ring nut

Illuminability no

Contact arrangement 2 NO

Contact function momentary

Contact system sliding bridge contact

Contact materials Ag
Lamp socket no

Other specifications

Ambient temp. operating max. +85 °C

Ambient temp. operating min. -25 °C

Flame class acc. to UL 94 V 0

Weight 14 g

Hot wire ignition acc. to IEC 60695-2-1 yes

Resistance to constant environment according to IEC 600 68-2-3 and 2-30

Storage temperature max. +90 °C

Storage temperature min. -40 °C

Operating life 50000

Degree of protection from front side IP40 (IP65 with sealing cap)

Resistance at variable environment according to IEC 600 68-2-14 and 2-33

Productinformatie

Artikelnummer	RAM1G
Merk	RAFI
Is on Sale	Nee

