

LIVE MIXER GIG-62 6 KANAALS

€ 135,00

Excl. BTW: € 111,57

Afbeeldingen



Beschrijving

The GIG-62 Mixing Console is packed with features that cannot be found in other consoles of its size: 2 mono (provided with ultra low noise microphone pre amplifiers and Phantom Power at +48 Volt) and 2 stereo input channels. Each of them are provided with a 3-band equalizer for HI, MID and LOW controls, as well as 1 auxiliary control, highly accurate 4-segment bar graph meters and 2-track inputs assignable to main mix, control room/phones or group outputs.

Specifications

Mono Channels

Mic Input: XLR balanced

Line input: 1/4- TRS balanced
Freq response: 10Hz ~ 55kHz, +/- 3dB
Distortion (THD=N): <0,03% @ 0dB, 22Hz ~ 22kHz
Gain range: 50dB
Input sensitivity: -35dBu ~ +15dBu
LOW Cut: 75Hz
SNR <-100dB
Phantom Power: +48V switchable

Stereo Channels

Mic Input: XLR balanced
Line input: 1/4- TRS/RCA unbalanced
Freq response: 10Hz ~ 55kHz, +/- 3dB
Distortion (THD=N): <0,03% @ 0dB, 22Hz ~ 22kHz
Gain range: 50dB
Input sensitivity: -20dBu ~ +20dBu
LOW Cut: 75Hz
SNR <-100dB
Phantom Power: +48V switchable

Channels EQ

High: +/- 15dB @ 12kHz
Mid: +/- 15dB @ 2,5kHz
Low: +/- 15dB @ 80Hz

Impedances

Microphone input: 1,8K Ohm
Other inputs: >10K Ohm
Tape output: 1K Ohm
All other outputs 120 Ohm

Power supply: AC 100- 240V 50Hz/60Hz

Power consumption: 40 Watt

Measurements: 244 x 196 x 60mm

Weight: 1,74 Kg

Productinformatie

| | |
|---------------|-----------|
| Artikelnummer | D2281 |
| Merk | DAP AUDIO |
| Is on Sale | Nee |

