

AUTORELAIS 1 X MAAK 12VDC 80R 70A

€ 6,95

Excl. BTW: € 5,74

Afbeeldingen



Beschrijving

Features

- High contact ratings 70A
- PCB terminals

Technical Specifications

Contact:	SPST-NO
Contact Material:	AgSnO ₂
Rated Current:	70A
Max. Switching Current:	75V DC
Operate/Release Time:	10/10ms

Testing Voltage Coil/Contact:	500V AC
Lifetime	
Mechanical:	10x10 ⁶ Operations
Electrical:	1x10 ⁵ Operations
Operating Temperature:	-40...+85°C
Weight Approx.:	47g

Coil Data

Part Nr.	U _N	U _{max.}	U _{An}	U _{Ab}	I _N	P _N	R _N
	[V DC]	[V]	[V]	[V]	[mA]	[mW]	[W]
FRC3-12F	12	18	7,8	1,2	150	1800	80

U_N = Rated Voltage, U_{max.} = Maximum Operating Voltage, U_{An} = Operate Voltage, U_{Ab} = Release Voltage, I_N = Rated Current, P_N = Rated Power, R_N = Coil Resistance; All Specifications Measured at 20°C

Productinformatie

Artikelnummer	R012D1MG
Merk	FIC
Is on Sale	Nee

