

RELAIS DIL REED 12VDC/500 OHM/12MA 1 X MAAK 10VA/0.5A 9 STUKS

€ 24,74

Excl. BTW: € 20,45

## Afbeeldingen



## Beschrijving

### Features

- Flux sealed construction
- Plug-in a 14-pole DIP/DIL-IC socket (see note)
- TTL-control possible
- DIP\_12D: High-profile, with integrated diode parallel to coil

### Technical Specifications

- Insulation Resistance (Coil/Contacts): 1012W
- Insulation (Coil/Contacts): 1500V DC
- Temperature Range: -20...+70°C
- Operate Time (incl. Bounce): 0,5ms
- Release Time: 0,1ms
- Vibration Resistance (10...2000Hz): 20G
- Soldering Temperature/Time: 260°C/5s

### Contact Data

- Configuration: SPST-NO
- Contact Resistance: 150mW
- Switching Capacity, Max.: 15W
- Switching Voltage, Max.: 200V DC
- Switching Current, Max.: 1,0A
- Current After Closure, Max.: 1,25A
- Breakdown Voltage, Min.: 250V DC

### Coil Data

- Coil Type: Polarized, Monostable

## Productinformatie

---

Artikelnummer	RO12D1MJ
Merk	ECE
Is on Sale	Nee

