

Eijlander Electronics Ede

..... THE BEST IN ELECTRONICS!

Zanderijweg 12,
6717BM Ede
T. 0318-757900

RELAIS DIL REED 24VDC/2K15 OHM/11MA 1 X MAAK 10VA/0.5A 9 STUKS

€ 27,50

Excl. BTW: € 22,73

Afbeeldingen



Beschrijving

Features

- Wash Tight
- Plug-in a 14-pole DIP/DIL-IC socket (see note)

Technical Specifications

- Insulation Resistance (Coil/Contacts), Min.: 1010W
- Insulation (Coil/Contacts): 1400V DC
- Storage Temperature: -55...+125°C
- Temperature Range: -40...+85°C
- Operate Time (incl. Bounce Time): 1,0ms
- Reset Time: 0,5ms
- Vibration Resistance (50...500Hz): 30G

Contact Data

- Configuration: SPST-NO
- Contact Resistance, Max.: 150mW

Switching Capacity, Max.: 10VA
Switching Voltage, Max.: 100V DC
Switching Current, Max.: 0,5A
Current After Closed Contact: 1,0A
Breakdown Voltage: 250V DC

Coil Data

Coil Type: Non-Polarized, Monostable

Productinformatie

Artikelnummer	R024D1MG
Merk	ECE
Is on Sale	Nee

