

GESCHAKELDE VOEDING SINGLE OUTPUT 60W 12V/5.0A

€ 31,94

Excl. BTW: € 26,40

Afbeeldingen



Beschrijving

MODEL S-60-12

OUTPUT:

DC VOLTAGE 12.0V

RATED CURRENT 5A

CURRENT RANGE 0 ~ 5A

RATED POWER 60W

RIPPLE & NOISE (max.) 120mVp-p

OUTPUT VOLTAGE ADJ. RANGE 10.8-13.2V

VOLTAGE TOLERANCE +/-1.0%

LINE REGULATION +/-0.5%

LOAD REGULATION +/-0.5%

SETUP, RISE TIME 300ms, 50ms/230VAC

HOLD TIME (Typ.) 80ms/230VAC at full load

INPUT:

VOLTAGE RANGE 88 ~ 264VAC

FREQUENCY RANGE 47 ~ 63Hz

EFFICIENCY(Typ.) 76%

AC CURRENT (Typ.) 1A/230VAC
INRUSH CURRENT (Typ.) COLD START 40A/230VAC
LEAKAGE CURRENT <3.5mA / 240VAC

PROTECTION:

OVER LOAD 110 ~ 150% rated output power

Protection type : Hiccup mode, recovers automatically after fault condition is

OVER VOLTAGE 13.8 ~ 16.2V Protection type : Hiccup mode, recovers automatically after fault condition is removed

Dimensions 99*97*36mm (L*W*H)

Productinformatie

Artikelnummer	S6012
Merk	MEANWELL
Is on Sale	Nee

