

HOORNSPEAKER 100V 15W 214X231MM

€ 125,01

Excl. BTW: € 103,31

Afbeeldingen



Beschrijving

Re-entrant horn speaker with 100 V transformer. Five-stage level adjustment for 100 V model via knob, in addition 20 Ohm possible. High sound pressure and wide range of frequency response guarantee excellent voice quality. Pivoting metal frame for mounting walls, ceilings, columns etc.

Typical applications:

- PA systems in factory halls, railway stations etc.
- outdoor PA

Attributes:

- functionally at low temperature according to EN 60068-2-1 (-25 °C; 96 h)
- up to the standards of the Germanischer Lloyd (requirements for electrical equipment / low temperature)
- 100 V transformer

Transformer matching 15; 10; 5; 3; 1 W; 20 Ohm

Sound pressure level 107 dB (1 W/1 m)

@ 1144 Hz

Frequency response 400- 5000 Hz

Mean sound pressure level 105 dB (1 W/1 m)

Max. sound pressure level 117 dB (15 W/1 m)

Opening angle (-6 dB) 42°/4000 Hz

Net weight 1,4 kg

Length of cable 0,6 m

Protective system IP 66

Temperature range -25 ... 70 °C

Colour RAL 7012

Productinformatie

| | |
|---------------|---------|
| Artikelnummer | DK8 |
| Merk | VISATON |
| Is on Sale | Nee |

