

GESCHAKELDE VOEDING SINGLE OUTPUT 49W 3.3V/15A

€ 31,50

Excl. BTW: € 26,03

Afbeeldingen



Beschrijving

MODEL RS-75-3.3

OUTPUT:

DC VOLTAGE 3.3V

RATED CURRENT 15A

CURRENT RANGE 0 ~ 15A

RATED POWER 49.5W

RIPPLE & NOISE (max.) 80mVp-p

OUTPUT VOLTAGE ADJ. RANGE 3 ~ 3.6V

VOLTAGE TOLERANCE +/-3.0%

LINE REGULATION +/-0.5%

LOAD REGULATION +/-1.0%
SETUP, RISE TIME 500ms, 30ms/230VAC
HOLD TIME (Typ.) 60ms/230VAC at full load

INPUT:

VOLTAGE RANGE 88 ~ 264VAC
FREQUENCY RANGE 47 ~ 63Hz
EFFICIENCY(Typ.) 71%
AC CURRENT (Typ.) 1.2A/230VAC
INRUSH CURRENT (Typ.) COLD START 40A/230VAC
LEAKAGE CURRENT <2mA / 240VAC

PROTECTION:

OVER LOAD 110 ~ 150% rated output power
Protection type : Hiccup mode, recovers automatically after fault condition is
OVER VOLTAGE 3.8 ~ 4.45V Protection type : Hiccup mode, recovers automatically after fault condition is removed

Dimensions 129*97*38mm (L*W*H)

Productinformatie

Artikelnummer	RS7503.3
Merk	MEANWELL
Is on Sale	Nee

