

**SPEAKER BREEDBAND 8 OHM 10/15W 130-20000HZ 84DB
50.5X90.5MMAFGESCHERMD**

€ 10,25

Excl. BTW: € 8,47

Afbeeldingen



Beschrijving

Magnetically shielded oval fullrange driver with a powerful magnetic drive, good efficiency and a very balanced frequency response. Due to the very good highrange reproduction and the small size any non-spacious application in the field of multimedia and Dolby Surround are possible. The SC 5.9 can furthermore be used as replacement part for internal TV speakers.

Typical applications:

- Multimedia systems
- Video monitoring screens
- TVs
- Computer terminals
- Control speaker for electronic devices

Attributes:

- Moisturised cone
- Metal basket
- Magnetically shielded

Rated power 10 W
Maximum power 15 W
Nominal impedance Z 8 Ohm
Frequency response 130- 20000 Hz
Mean sound pressure level 84 dB (1 W/1 m)
Opening angle (-6 dB) 180°/4000 Hz hor.
131°/4000 Hz ver.
Excursion limit +/-1,5 mm
Resonance frequency fs 193 Hz
Magnetic induction 0,9 T
Magnetic flux 120 μWb
Height of front pole-plate 3 mm
Voice coil diameter 14 mm
Height of winding 4 mm
Cutout diameter 43 x 82 mm (oval)
Net weight 0,214 kg
D.C. resistance Rdc 7,0 Ohm
Mechanical Q factor Qms 7,52
Electrical Q factor Qes 1,5
Total Q factor Qts 1,25
Equivalent volume Vas 0,4 l
Effective piston area Sd 26,5 cm²
Dynamically moved mass Mms 1,5 g
Force factor Bxl 2,5 Tm
Inductance of the voice coil L 0,4 mH
Temperature range -25 ... 70 °C

Productinformatie

| | |
|---------------|---------|
| Artikelnummer | SC5.9 |
| Merk | VISATON |
| Is on Sale | Nee |

