

EINDBUIS 8P OKTAL OUTPUT PENTODE

€ 39,95

Excl. BTW: € 33,02

Afbeeldingen



Beschrijving

A. F. OUTPUT PENTODE

Base: OCTAL

U_f = 6,3 V

I_f = ca 1,5 A

Typical

characteristic:

U_a = 250 V

$U_{g3} = 0 \text{ V}$
 $U_{g2} = 265 \text{ V}$
 $U_{g1} = -10 \text{ V}; -13,5 \text{ V}$
(for EL34)
 $-13,5 \text{ V}; -16,5 \text{ V}$
(for E34L)
 $I_a = 100 \text{ mA}$
 $I_{g2} = 14,9 \text{ mA}$
 $S = 11 \text{ mA/V}$
 $R_i = 15 \text{ k}\Omega$
 $i_{g2/g1} = 11$
 $I_{az} (U_{g1} = -30 \text{ V}) < 7 \text{ mA}$
Limiting values:
 $U_{a0} = 2000 \text{ V}$
 $U_a = 800 \text{ V}$
 $W_a(\text{max}) = 25 \text{ W}$
 $U_{g20} = 800 \text{ V}$
 $U_{g2} = 450 \text{ V}$
 $W_{g2}(\text{max}) = 8 \text{ W}$
 $I_k = 150 \text{ mA}$
 $U_{k/f} = 100 \text{ V}$
 $R_{k/f} = 20 \text{ k}\Omega$
Capacitances:
 $c_{g1} = 15,5 \text{ pF}$
 $c_a = 10 \text{ pF}$
 $c_{a/g1} = 1,3 \text{ pF}$

Productinformatie

Artikelnummer	EL34
Merk	JJ ELECTRONIC
Is on Sale	Nee

