

HDMI 1.4 MALE - MALE 100M GLASVEZELKABEL

€ 388,41

Excl. BTW: € 321,00

Afbeeldingen



Beschrijving

HDMI Fiber Optic Cable fully supports HDMI 1.4 High Speed specification with light weight, flexible and elegant fiber cable. With advanced optical engine embedded, his cable provides full HDMI signal integrity, support up to 300m maximum length, plug and play. The fiber optic cable has a space and weight saving compared to copper cables: Based on a 30m cable about 80% weight reduction (0.4kg vs. 2.5kg) and a 3-fold smaller perimeter size (11mm vs. 33mm).

Easy to use, Reliable
Abel to install the cable duct

Works with all HDMI connected devices

Various lengths available, in lengths from 10 feet (3m) to 1000 feet (300m).

Applications: Home Theatre, Conference Room, Auditorium, Equipment Display, BluRay, 3D video, Projector, Set-up box, DVR, Game Consoles and Computer, Security systems, LED Sign Boards, Panel information displays for airports, stadiums and outdoor advertising

Required Power for receiver 5V DC (USB Port)

Operating Temperature: 0~50°C, Storage Temperature: -20~70°C, Relative Humidity: 10~80%

HDCP 1.1 Fully Support bi-directional EDID and HDCP communication

Supported Resolution & Distance: HDTV : 480p, 720p, 1080i and 1080p with 12bit deep colour, 4K, 3DFull HD 1920 x 1080

Connectors: HDMI type A on both sides, USB connector for the power supply of the receiver unit, Cable Type: Fully fiber optic, no copper

Minimum Cable Bending Radius: 20mm

Tensile Strength: 55lb / 25kg

To keep system working properly, always connect the cable \"Source\" end toward A/V source devices such as DVD player...etc. and always connect the cable \"Display\" end toward A/V sink devices such as TV...etc.

Note: This cable Doesn' t Support HEAC (HDMI Ethernet and Audio Return Channel) Feature.

Productinformatie

| | |
|---------------|------------|
| Artikelnummer | GQ3770/100 |
| Merk | Brand |
| Is on Sale | Nee |

