

**RELAIS SOLID STATE 24-480VAC 75A INPUT 3-32VDC (THYRISTOR
UITGANG)**

€ 89,43

Excl. BTW: € 73,91

Afbeeldingen



Beschrijving

Input circuit

Control voltage range 3...32 VDC

Control current max. 22 mA

Turn-off voltage min. 1 VDC

Input resistance Constant current

Output circuit

Load voltage range 24...480 VAC

Peak-off-state voltage 1200 V_{drm}

Off-state leakage current

Load current range 0,4...75A

Surge current 1 half wave 910 A_{peak}

I²t for fusing 4150 A²s

On-state voltage 1,6 V_{peak}

Off-state (static) dv/dt 1000 V/μs

Snubber 47 W / 22 nF

General data

Turn-on time max. 11 ms 0,1 ms

Turn-off time max. 11 ms

Line frequency range 47...63 Hz

Isolation volt. between input/output 4.000 V
Isolation volt. between input-output/base 2.500 V
Isolation resistance 50 MW
Operation temperature -20...+80 °C
Recommended varistor SIOV-S20 K230
10 mA eff.
Approvals cULus, VDE

Productinformatie

Artikelnummer	WG480D75Z
Merk	COMUS
Is on Sale	Nee

