

## DIN 41612 96P A+B+C FEMALE PRINT HAAKS

€ 4,36

Excl. BTW: € 3,60

### Afbeeldingen



### Beschrijving

Insulation Shell: Glass Filled Polyamide (PBT), (UL94V-0)

Contact Material

Male Connector: Brass

Female Connector: Copper Alloy

Contact Surface

Plug-in Side: Gold Over Nickel

Solder Side: Tin-plated

Mating and Withdraw Force, Max.:

32-Pole: 30N

64-Pole: 60N

96-Pole: 90N

Air and Creepage, Min.: 1,2mm

Operating Voltage: 250V AC

Test Voltage

Between Contacts

P = 5,08: 1550VRMS

P = 2,54: 1000VRMS

Between Contacts and Shell: 1550VRMS

Rated Current

20°C: 2A

70°C: 1A

100°C: 0,5A

Contact Resistance:  $\diamond$ 20mW

After 400 Transmission Cycles:  $\diamond$ 40mW

Insulation Resistance  
Between Adjacent Contacts (100VAC):  $3 \times 10^{12} \text{W}$   
Temperature Range:  $-55 \dots +125^\circ\text{C}$   
Class: 3

## Productinformatie

---

Artikelnummer	96.6821R
Merk	Brand
Is on Sale	Nee

