

## REGELBARE VOEDING 1X 3-15V 60A DIGITAAL

€ 399,00

Excl. BTW: € 329,75

### Afbeeldingen



### Beschrijving

#### Features

- Total max. continuous output current 60A (SPS-9600) / 30A (SPS-9602)
- Main Output / Remote Sensing / Remote Control / terminals at the back
- Front terminals 5A (SPS-9600) / 3A (SPS-9602) limiting
- Adjustable output voltages 1 to 15Vdc (SPS-9600) / 1 to 30Vdc (SPS-9602)
- Remote Sensing for remote point of regulation
- Remote control terminals for output voltage adjustment and \*on/off\*

Light weight and small size  
Overload / Over-temperature / Short Circuit Protections  
Constant Current Limiting Protection with LED indicator showing overloading  
Variable speed thermally controlled fan  
High RFI stability  
Active Power Factor Correction (P.F. > 0.97)  
Housing are available in (Pantone warm grey 1C or Pantone dark grey 433C )

\* Remote output on/off is an added function for protection after October 2004\*

#### Specifications

Variable Output Voltage 1 - 15 V DC  
Total Rated Output Current ( Main output + Front Output ) 60A  
Rated Output current ( Main Output ) 60A  
Rated Output Current ( Front Output ) 5A  
Load Regulation ( Main Output ) 0.1% + 5mV  
Line Regulation ( Main Output ) 0.05% + 3mV  
Ripple & Noise ( peak-peak ) 50mV p-p  
Input Voltage 230V AC / 50Hz (or on request)  
Efficiency > 85%  
Meter Type LED Meter  
Voltmeter Range 3 digit display  
Ammeter Range 3 digit display  
Meter Accuracy  $\pm 1\%$  +1 count  
Protection Devices Overload (Constant Current Limiting), Short Circuit, Over Temperature, OVP  
Cooling System Variable Speed Thermally Control Fan  
Special feature Remote Sensing, Remote output voltage control and \*on/off\*  
\* Remote on/off only for production after October 2004 \*  
Approvals CE-EMC : EN 55022, CE-LVD: EN 60950  
Dimensions ( W x H x D ) 220 x 110 x 360 (mm)  
Weight 5.8 Kgs  
Remarks Power factor correction  $\geq 0.97$  at optimal load

## Productinformatie

Artikelnummer	SPS9600
Merk	Brand
Is on Sale	Nee

