

ACCULADER 28,8V 12.5A VOOR LEAD-ACID ACCU'S

€ 155,00

Excl. BTW: € 128,10

Afbeeldingen



Beschrijving

Features

- 3 stage charger for lead acid batteries
- Input voltage range: 90...132V/180...264V AC
- AC 115/230VAC selected by switch
- Overload protection, constant current limiting, reset: auto recovery
- Protection: reverse polarity/short circuit/over voltage/over temperature
- 2 color LED loading indicator

Operating Temperature: -10...+60°C

Storage Temperature: -40...+85°C

Overload Protection: 90...110%

Insulation Voltage

I/P-O/P: 3000V AC

I/P-FG: 1500V AC

O/P-FG: 500V AC

Insulation Resistance

I/P-O/P, I/P-FG, O/P-FG: 500V DC: 100MΩ

Dimensions: 253x135x48,5mm

Weight: 1,50kg

I/P = Input, O/P = Output, FG = Frame Ground

Input

Input Voltage: 90...132V AC / 180...264VAC

47...63Hz

AC Current (230V): 3.5A

In-Rush Current, Cold Start (230V): 60A

Output

Boost Charge Voltage: 28,8V

Float Charge Voltage: 27,2V

Output Current, max: 12,5A

Efficiency: 86%

Recommended Battery Capacity: 40...125Ah

Productinformatie

Artikelnummer	PB360P24
Merk	MEANWELL
Is on Sale	Nee

