
RELAIS BISTABIEL (2 SPOELEN) 12VDC 2 X WISSEL 250VAC/8A

€ 7,95

Excl. BTW: € 6,57

Afbeeldingen



Beschrijving

Features

- SPDT or DPDT contact configurations
- Bistable with 2 coils
- 5kV/10mm coil-contact, protection class II
- Low height 15,7mm

Technical Specifications

- 12Vdc (min. 8,4Vdc)
- 50mA
- 240 Ohm

Insulation (to IEC 60664): C/250; B/400

Rated Voltage: 250V

Pollution Degree: 3

Overvoltage Category: III

Dielectric Strength

Coil/Contact: 5000Veff

Open Contact: 1000Veff

Clearance/Creepage: 10/10mm

Temperature Range: -40...+85°C

Vibration Resistance (30...500 Hz): 3/5G

Contact Data

Contact Material: AgNi 90/10

Rated/Breaking Voltage (Ohmic Load), Max.8A/250V AC

Switching Voltage, Max.: 250V AC/440V AC

Breaking Capacity AC, Max. 2000VA

Mechanical Life 2x10⁵ Operations

Productinformatie

Artikelnummer	RB012D2WB
Merk	TYCO ELECTRONICS
Is on Sale	Nee

