


## GESCHAKELDE VOEDING 40W 48V/0,84A IP64

€ 49,50

Excl. BTW: € 40,91

### Afbeeldingen



### Beschrijving

#### Features

- Universal input
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- IP64, for indoor and outdoor installations
- Suitable for LED lighting and moving sign applications
- Adjustable output voltage
- Adjustable output current
- EN61000-3-2, Class C, EN55015, EN61347-1, EN61347-2-13

#### Technical Specifications

Input Voltage: 90...305V AC (47...63Hz)/ 127...431V DC  
Input Inrush Current, Max.: 70A  
Over Current Protection: 95...108%  
Withstand Voltage  
I/P-O/P: 3750V AC

I/P-FG: 1880V AC  
O/P-FG: 500V AC  
Operating Temperature: -40...+50°C  
Weight: 350g  
I/P = Input, O/P = Output, FG = Frame Ground

Output Voltage: 48V  
Output Voltage Adjustment: 44...51V  
Output Current Adjustment: 0,5...0,84A  
Output Power: 40,3W  
Output Voltage Tolerance: 1%  
Ripple & Noise:300mVp-p  
Typ. Efficiency: 90%

## Productinformatie

---

Artikelnummer	HLN40H48A
Merk	MEANWELL
Is on Sale	Nee

