

## DIN-RAIL 22.5MM VOEDING 20W 15V/1.34A

€ 18,95

Excl. BTW: € 15,66

### Afbeeldingen



### Beschrijving

MODEL MDR-20-15

#### OUTPUT:

DC VOLTAGE 15V

RATED CURRENT 1.34

CURRENT RANGE 0~ 1.34A

RATED POWER 20W

RIPPLE & NOISE (max.) Note.2 120mVp-p

VOLTAGE ADJ. RANGE 13.5~16.5V

VOLTAGE TOLERANCE Note.3 +/-1.0%

LINE REGULATION +/-1.0%

LOAD REGULATION +/-1.0%

SETUP, RISE TIME 500ms, 30ms/230VAC at full load

HOLD UP TIME (Typ.) 50ms/230VAC at full load

#### INPUT:

VOLTAGE RANGE 85 ~ 264VAC

FREQUENCY RANGE 47 ~ 63Hz

EFFICIENCY (Typ.) 81%  
AC CURRENT (Typ.) 0.35A/230VAC  
INRUSH CURRENT (Typ.) COLD START 40A/230VAC  
LEAKAGE CURRENT <1mA / 240VAC

**PROTECTION:**

**OVERLOAD**

105 ~ 160% rated output power

Protection type : Constant current limiting, recovers automatically after fault condition is removed

**OVER VOLTAGE 17.25 - 20.25V**

Protection type : Shut down o/p voltage, re-power on to recover.

FUNCTION DC OK SIGNAL (max.) 11.5-16.5V/40mA

DIMENSION: 22.5\*90\*100mm (W\*H\*D)

## Productinformatie

---

Artikelnummer	MDR2015
Merk	MEANWELL
Is on Sale	Nee

