

Zanderijweg 12, 6717BM Ede T. 0318-757900

DC JOLLY SLIM LED DRIVER 47VDC 350-900MA 32W 237X30X21MMDIMBAAR 1-10V & PUSH

€ 37,50 Excl. BTW: € 30,99

Afbeeldingen



Beschrijving





JOLLY SLIM 1...10 V & PUSH Direct current dimmable electronic drivers multivoltage-multicurrent for power LED and LED modules

Driver for built-in use.

Multi-power driver supplied with dip-switch for

the selection of the output current

Active Power Factor Corrector.

Light regulation 0-100% by means of PUSH

function (L mains voltage: 170 Kohm):

- a short push to turn on and off;

- a longer push to increase or decrease light intensity;

- regulation automatically stops at minimum and maximum values;

- for another on, regulation or off command, release the push button and give the desired command again.

Maximum length of the cable, from push button to last driver, must be max. 15 m. In case of applications where the cable is longer than 15 m, keep this separate from the 110-240 Volt mains cable.

Synchronization cable supplied separately. Max. 10 drivers synchronization, is possible

command only one driver (1Master + 9Slaves). ATTENTION: only use normally open push buttons with no incorporated warning light. Light regulation O-100% by means of PUSH function, 1...10 V interface (I=0,35 mA) or 100 Kohm potentiometer (1...10 Vdc source with double or reinforced insulation with respect to AC mains). For regulations see page 104-105.

Current regulation ±5% including temperature variations.

It can be used for lighting equipment in protection class I and II.

Ultra compact size.

Driver can be secured with slot for screws. Protections:

- against overheating and short circuits;

- against mains voltage spikes;

- against overloads.

IP67 cover available upon request

(code 180066/390).

Can be switched on and off on secondary circuit for power LED.

Productinformatie

Artikelnummer	122680
Merk	TCI
Is on Sale	Nee

