

DIN-RAIL 110MM VOEDING 960W 48V/20A

€ 299,00

Excl. BTW: € 247,11

Afbeeldingen



Beschrijving

- Three-Phase 340 ~ 550VAC wide range input
(Dual phase operation possible)
- Width only 110mm
- High efficiency 94.5% and low power dissipation
- Protections: Short circuit / Overload / Over voltage / Over temperature
- Cooling by free air convection
- Built-in constant current limiting circuit
- Can be installed on DIN rail TS-35/7.5 or 15
- UL508(industrial control equipment)approved

EN61000-6-2(EN50082-2) industrial immunity level
Current sharing up to 3840W(3+1)
Built-in DC OK relay contact
100% full load burn-in test
Built-in active PFC function compliance to EN61000-3-2

Technical Specifications

Input Voltage: Three-Phase 340 ~ 550VAC (Dual phase operation possible) 480 ~ 780VDC
Input Inrush Current, Max.: 60A

uitgangsspanning: 48V +/-1.0%
uitgangsstroom: 20A
max. vermogen: 960W
afmetingen: 110 x 125,2 x 150mm
gewicht: 2,47kg
werktemperatuur: -30°C ~ 70°C

Productinformatie

Artikelnummer	TDR96048
Merk	MEANWELL
Is on Sale	Nee

