

## DIN-RAIL 22.5MM VOEDING 10W 5V/2.0A

€ 16,95

Excl. BTW: € 14,01

### Afbeeldingen



### Beschrijving

Universal AC input/Full range  
Protections: Short circuit / Overload / Over voltage  
Cooling by free air convection  
Can be installed on DIN rail TS-35/7.5 or 15  
NEC class 2 / LPS compliant  
Built in DC OK active signal  
LED indicator for power on  
No load power consumption<0.75W



100% full load burn-in test

#### Technical Specifications

Input Voltage: 85...264V AC (47...63Hz) 120...370V DC

Input Inrush Current, Max.: 70A

Leakage Current, Max.: 1mA

No Load Power Consumption, Max.: 0,75W

Over Load Protection: >105%

Withstand Voltage

I/P-O/P: 3000V AC

I/P-FG: 1500V AC

O/P-FG: 500V AC

Operating Temperature: -20...+70°C

uitgangsspanning: 5V +/-5%

uitgangsstroom: 2.0A

max. vermogen: 10W

afmetingen: 22.5 x 90 x 100mm

gewicht: 170g

werktemperatuur: -20°C ~ 70°C

#### Productinformatie

Artikelnummer	MDR105
Merk	MEANWELL
Is on Sale	Nee

