

GESCHAKELDE VOEDING SINGLE OUTPUT 25W 15V/1.7A

€ 16,50

Excl. BTW: € 13,64

Afbeeldingen



Beschrijving

MODEL RS-25-15

Universal AC input / Full range
Protections: Short circuit / Overload / Over voltage
Cooling by free air convection
LED indicator for power on
100% full load burn-in test
All using 105C long life electrolytic capacitors
Withstand 300VAC surge input for 5 second
High operating temperature up to 70
Withstand 5G vibration test
High efficiency, long life and high reliability

OUTPUT:
DC VOLTAGE 15.0V

RATED CURRENT 1.7A
CURRENT RANGE 0 ~ 1.7A
RATED POWER 25.5W
RIPPLE & NOISE (max.) 120mVp-p
OUTPUT VOLTAGE ADJ. RANGE 13.5-16.5V
VOLTAGE TOLERANCE +/-1.0%
LINE REGULATION +/-0.5%
LOAD REGULATION +/-0.5%
SETUP, RISE TIME 1200ms, 23ms/230VAC
HOLD TIME (Typ.) 80ms/230VAC at full load

INPUT:

VOLTAGE RANGE 88 ~ 264VAC
FREQUENCY RANGE 47 ~ 63Hz
EFFICIENCY(Typ.) 82%
AC CURRENT (Typ.) 0.4A/230VAC
INRUSH CURRENT (Typ.) COLD START 30A/230VAC
LEAKAGE CURRENT <0.2mA / 240VAC

PROTECTION:

OVER LOAD 110 ~ 180% rated output power

Protection type : Hiccup mode, recovers automatically after fault condition is removed

OVER VOLTAGE 17.25 ~ 20.25V Protection type : Hiccup mode, recovers automatically after fault condition is removed

Dimensions 78*51*28mm (L*W*H)

Productinformatie

Artikelnummer	RS2515
Merk	MEANWELL
Is on Sale	Nee

