

**SPEAKER BREEDBAND 200-15000HZ 80HM 2/3W 60MM
VOCHTBESTENDIG**

€ 8,25

Excl. BTW: € 6,82

Afbeeldingen



Beschrijving

Technical Data:

Rated power 2 W

Maximum power 3 W

Nominal impedance Z 50 Ohm

Frequency response 200- 15000 Hz

Mean sound pressure level 86 dB (1 W/1 m)

Opening angle (-6 dB) 109°/4000 Hz

Excursion limit +/-1,5 mm

Resonance frequency fs 300 Hz

Magnetic induction 0,7 T

Magnetic flux 45 μWb

Height of front pole-plate 2 mm

Voice coil diameter 10 mm

Height of winding 2,5 mm

Cutout diameter 60 mm

Net weight 0,05 kg

Protective system IP 65 *)

Temperature range -40 ... 80 °C

Technical Data:

Rated power 2 W

Maximum power 3 W

Nominal impedance Z 8 Ohm

Frequency response 200- 15000 Hz

Mean sound pressure level 86 dB (1 W/1 m)
Opening angle (-6 dB) 109°/4000 Hz
Excursion limit +/-1,5 mm
Resonance frequency f_s 300 Hz
Magnetic induction 0,7 T
Magnetic flux 45 μ Wb
Height of front pole-plate 2 mm
Voice coil diameter 10 mm
Height of winding 2,5 mm
Cutout diameter 60 mm
Net weight 0,05 kg
Protective system IP 65 *)
Temperature range -40 ... 80 °C

Productinformatie

| | |
|---------------|---------|
| Artikelnummer | K64WP/8 |
| Merk | VISATON |
| Is on Sale | Nee |

