

---

**RELAIS BISTABIEL (2 SPOELEN) 24VDC 1 X WISSEL 250VAC/16A**

**€ 6,95**

Excl. BTW: € 5,74

## Afbeeldingen

---



## Beschrijving

---

### Features

- SPDT or DPDT contact configurations
- Bistable with 2 coils
- 5kV/10mm coil-contact, protection class II
- Low height 15,7mm

### Technical Specifications

- 24Vdc (min. 16,8Vdc)
- 27mA
- 886 Ohm

- Insulation (to IEC 60664): C/250; B/400
- Rated Voltage: 250V
- Pollution Degree: 3
- Overvoltage Category: III

### Dielectric Strength

- Coil/Contact: 5000Veff
- Open Contact: 1000Veff
- Clearance/Creepage: 10/10mm
- Temperature Range: -40...+85°C
- Vibration Resistance (30...500 Hz): 3/5G

### Contact Data

- Contact Material: AgNi 90/10
- Rated/Breaking Voltage (Ohmic Load), Max. 16A/250V AC
- Switching Voltage, Max.: 250V AC/440V AC
- Breaking Capacity AC, Max. 4000VA
- Mechanical Life 5x10<sup>5</sup> Operations

## Productinformatie

---

Artikelnummer	RBO24D1WB
Merk	TYCO ELECTRONICS
Is on Sale	Nee

