

LED VOEDING 24V/1,3A 31,2W OPEN FRAME

€ 22,95

Excl. BTW: € 18,97

Afbeeldingen



Beschrijving

Features

- Universal input
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Open-frame
- Built-in active PFC function
- Suitable for LED lighting and moving sign applications

Technical Specifications

Input Voltage: 90...264V AC (47...63Hz)

Input Inrush Current, Max.: 40A

Over Load Protection: 100...110%

Withstand Voltage

(I/P-O/P): 3750V AC

(I/P-FG): 1880V AC

(O/P-FG): 500V AC

I/P = Input, O/P = Output, FG = Frame Ground

Operating Temperature: -30...+70°C

Weight: 110g

Dimensions 101,6x50,8x25mm (LxWXH)

Output Voltage: 24Vdc

Output Current Range: 0 - 1,3A

Current Adjustment: 0,975 - 1,3A
Output Power: 31,2W
Output Voltage Tolerance: 10%
Ripple & Noise: 2,4Vp-p
Typ. Efficiency: 85,5%

Productinformatie

| | |
|---------------|----------|
| Artikelnummer | PLP3024 |
| Merk | MEANWELL |
| Is on Sale | Nee |

