

JOLLY MD PUSH LED DRIVER 12-47VDC 350-750MA 32W 166X47X35MMDIMBAAR MET STANDAARD DIMMER

€ 47,50 Excl. BTW: **€** 39,26

Afbeeldingen



Beschrijving





Direct current dimmable electronic drivers multivoltage-multicurrent for power LED and LED modules

IP20 independent driver, for indoor use.

Multi-power driver supplied with dip-switch for the selection of the output current

Active Power Factor Corrector.

Regulating driver with \"phase cut-off\" dimmer IGBT and TRIAC.

Light regulation 0-100% by means of PUSH function (mains voltage):

- a short push to turn on and off;
- a longer push to increase or decrease light intensity;
- regulation automatically stops at minimum and maximum values;
- for another on, regulation or off command, release the push button and give the desired command again;
- dimming level memory at mains restore.

Maximum length of the cable, from push button to last transformer, must be max. 15 m. In case of applications where the cable is longer than 15 m, keep this separate from the 110-240 Volt mains cable.

Synchronization cable is separately supplied. Max. 10 drivers synchronization, is possible command only one driver (1 Master + 9 Slaves).

ATTENTION: only use normally open push

buttons with no incorporated warning light.

Light regulation 0-100% by means of PUSH.

Class II protection against electric shock

following direct or indirect contact.

Current regulation $\pm 5\%$ including temperature variations.

Supplied with terminal cover and cable retainer.

Input and output terminal blocks on opposite sides (terminal area 2,5 mm2).

Doble terminal blocks to loop other driver.

Clamping screws on primary and secondary circuits for cables with diameter:

min. 3 mm - max. 8 mm.

Driver can be secured with slot for screws.

Protections:

- against overheating and short circuits;
- against mains voltage spikes;
- against overloads.

Thermal protection = C.5.a.

Can be switched on and off on secondary

Productinformatie

Artikelnummer	122260
Merk	TCI
Is on Sale	Nee

