

GESCHAKELDE VOEDING SINGLE OUTPUT 720W 12V/60A 1HE

€ 335,00

Excl. BTW: € 276,86

Afbeeldingen



Beschrijving

Universal AC input / Full range
AC input active surge current limiting
Built-in 5V/0.5A auxiliary power
Built-in active PFC function, PF>0.95
Protections: Short circuit / Overload / Over voltage / Over temperature
Output voltage can be trimmed between 40 ~ 110% of the rated output voltage
Forced air cooling by built-in DC fan
High power density 10.7w/inch
1U low profile 41mm
Active current sharing up to 4000W(3+1)
DC OK Signal
Built-in remote ON-OFF control
Built-in remote sense function

OUTPUT
DC VOLTAGE: 12V

RATED CURRENT: 60A
CURRENT RANGE: 0 ~ 60A
RATED POWER: 720W
VOLTAGE ADJ. RANGE: 10 ~ 13.5V

INPUT

VOLTAGE RANGE: 90 ~ 264VAC
FREQUENCY RANGE: 47 ~ 63Hz
POWER FACTOR (Typ.): 0.95/230VAC
EFFICIENCY (Typ.): 83%
AC CURRENT (Typ.): 6A/230VAC
INRUSH CURRENT (Typ.): 40A/230VAC
LEAKAGE CURRENT: <2.0mA / 240VAC

Productinformatie

Artikelnummer	RSP100012
Merk	MEANWELL
Is on Sale	Nee

