

Eijlander Electronics Ede

..... THE BEST IN ELECTRONICS!

Zanderijweg 12,
6717BM Ede
T. 0318-757900

SPEAKER BREEDBAND 4 OHM 2/4W 220-20000HZ 81DB
41X71MMAFGESCHERMD

€ 7,95

Excl. BTW: € 6,57

Afbeeldingen



Beschrijving

Magnetically shielded oval fullrange driver with good efficiency and balanced frequency response with a clear highrange reproduction. Extremely small size due to a neodymium magnet system. Applicable as built-in speaker in TV\'s and PC\'s

with very small mounting space.

Typical applications:

- Video monitoring screens
- TVs
- Control speaker for electronic devices

Rated power 2 W

Maximum power 4 W

Nominal impedance Z 4 Ohm

Frequency response 220- 20000 Hz

Mean sound pressure level 81 dB (1 W/1 m)

Opening angle (-6 dB) 180°/4000 Hz hor.

180°/4000 Hz ver.

Excursion limit +/-0,5 mm

Resonance frequency f_s 420 Hz

Magnetic induction 0,7 T

Magnetic flux 60 μ Wb

Height of front pole-plate 2 mm

Voice coil diameter 14 mm

Height of winding 2 mm

Cutout diameter 35 x 65 mm (oval)

Net weight 0,041 kg

D.C. resistance R_{dc} 3,8 Ohm

Mechanical Q factor Q_{ms} 4,43

Electrical Q factor Q_{es} 6,55

Total Q factor Q_{ts} 2,64

Equivalent volume V_{as} 0,9

Effective piston area S_d 45 cm²

Dynamically moved mass M_{ms} 0,7 g

Force factor B_{xl} 1,2 Tm

Inductance of the voice coil L 0,2 mH

Temperature range -25 ... 70 °C

Productinformatie

Artikelnummer	SC4.7ND4
Merk	VISATON
Is on Sale	Nee

