

**SPEAKER BREEDBAND 4 OHM 3/4W 150-17000HZ 82DB
50.5X90.5MMAFGESCHERMD**

€ 10,74

Excl. BTW: € 8,88

Afbeeldingen



Beschrijving

Magnetically shielded oval fullrange driver with good efficiency and balanced frequency response with a clear highrange reproduction. Extremely small size due to a neodymium magnet system. Applicable as built-in speaker in TV's and PC's with very small mounting space.

Typical applications:

- Video monitoring screens
- TVs
- Control speaker for electronic devices

Attributes :

- Moisturised cone
- Metal basket
- Magnetically shielded

Rated power 3 W
Maximum power 4 W
Nominal impedance Z 4 Ohm
Frequency response 150- 17000 Hz
Mean sound pressure level 82 dB (1 W/1 m)
Opening angle (-6 dB) 180°/4000 Hz hor.
131°/4000 Hz ver.
Excursion limit +/-1 mm
Resonance frequency fs 243 Hz
Magnetic induction 0,75 T
Magnetic flux 100 μ Wb
Height of front pole-plate 3 mm
Voice coil diameter 14 mm
Height of winding 4 mm
Cutout diameter 43 x 82 mm (oval)
Net weight 0,06 kg
D.C. resistance Rdc 3,8 Ohm
Mechanical Q factor Qms 9,23
Electrical Q factor Qes 8,03
Total Q factor Qts 4,3
Equivalent volume Vas 0,3 l
Effective piston area Sd 26,5 cm²
Dynamically moved mass Mms 1,3 g
Force factor Bxl 1,0 Tm
Inductance of the voice coil L 0,2 mH
Temperature range -25 ... 70 °C

Productinformatie

Artikelnummer	SC5.9ND/4
Merk	VISATON
Is on Sale	Nee

