

DC-DC CONVERTER 36-72V:5V 3A IN BEHUIZING

€ 20,95

Excl. BTW: € 17,31

Afbeeldingen



Beschrijving

15W Single Output DC-DC Converter
2:1 wide input range
Protections: Short circuit/Over load /voltage
Built-in EMI filter, low ripple noise
100% full load burn-in test
Low cost
High reliability

OUTPUT

DC VOLTAGE: 5V
RATED CURRENT: 3,0A
CURRENT RANGE: 0 ~ 3.0A
RATED POWER: 15W
RIPPLE & NOISE (max.) Note.2: 100mVp-p
VOLTAGE ADJ. RANGE: 4.75 ~ 5.5VDC
VOLTAGE TOLERANCE Note.3: +/- 2.0%
LINE REGULATION: +/- 0.5%
LOAD REGULATION: +/- 0.5%
SETUP, RISE, HOLD UP TIME: 2.5s, 50ms, ---12VDC/24VDC/48VDC at full load

INPUT

VOLTAGE RANGE: 36 ~ 72VDC
INPUT EFFICIENCY (Typ.): 75%
DC CURRENT: 0.45A/48VDC

DIMENSION: 78x51x28mm (LxWxH)

Productinformatie

Artikelnummer	SD15C5
Merk	MEANWELL
Is on Sale	Nee

