

DC-DC CONVERTER 9,2-18V:5V 5.0A IN BEHUIZING

€ 34,50

Excl. BTW: € 28,51

Afbeeldingen



Beschrijving

25W Single Output DC-DC Converter
2:1 wide input range
Protections: Short circuit / Overload / Over voltage
1500VDC I/O isolation
Built-in EMI filter, low ripple noise
100% full load burn-in test
Fixed switching frequency at 83KHz
Low cost
High reliability

OUTPUT

DC VOLTAGE: 5V
RATED CURRENT: 5,0A
CURRENT RANGE: 0 ~ 5.0A
RATED POWER: 25W
RIPPLE & NOISE (max.) Note.2: 100mVp-p
VOLTAGE ADJ. RANGE: 4.5 ~ 5.5VDC
VOLTAGE TOLERANCE Note.3: +/- 2.0%
LINE REGULATION: +/- 0.5%
LOAD REGULATION: +/- 0.5%
SETUP, RISE, HOLD UP TIME: 2.5s, 50ms, ----- at full load

INPUT

VOLTAGE RANGE: 9.2 ~ 18VDC
INPUT EFFICIENCY (Typ.): 71%
DC CURRENT: 3.2A/12V

DIMENSION: 99x97x36mm (LxWxH)

Productinformatie

Artikelnummer	SD25A5
Merk	MEANWELL
Is on Sale	Nee

