

## DC-DC CONVERTER 36-72V:5V 5.0A IN BEHUIZING

€ 34,50

Excl. BTW: € 28,51

### Afbeeldingen



### Beschrijving

25W Single Output DC-DC Converter  
2:1 wide input range  
Protections: Short circuit / Overload / Over voltage  
1500VDC I/O isolation  
Built-in EMI filter, low ripple noise  
100% full load burn-in test  
Fixed switching frequency at 83KHz  
Low cost  
High reliability

OUTPUT

DC VOLTAGE: 5V

RATED CURRENT: 5,0A

CURRENT RANGE: 0 ~ 5.0A

RATED POWER: 25W

RIPPLE & NOISE (max.) Note.2: 100mVp-p

VOLTAGE ADJ. RANGE: 4.5 ~ 5.5VDC

VOLTAGE TOLERANCE Note.3: +/- 2.0%

LINE REGULATION: +/- 0.5%

LOAD REGULATION: +/- 0.5%

SETUP, RISE, HOLD UP TIME: 2.5s, 50ms, ----- at full load

INPUT

VOLTAGE RANGE: 36 ~ 72VDC

INPUT EFFICIENCY (Typ.): 74%

DC CURRENT: 3.2A/12V

DIMENSION: 99x97x36mm (LxWxH)

Productinformatie

---

Artikelnummer	SD25C5
Merk	MEANWELL
Is on Sale	Nee

