

**GESCHAKELDE VOEDING SINGLE OUTPUT 155W 36V/4,3A MET  
INGEBOUWD REMOTESIGNAAL VOOR AAN/UIT CONTROLE**

**€ 95,00**

Excl. BTW: € 78,51

**Afbeeldingen**



**Beschrijving**

- Universal AC input / Full range
- Built-in active PFC function, PF>0.95
- High efficiency up to 88%
- Withstand 300VAC surge input for 5 seconds
- Protections: Short circuit / Overload / Over voltage / Over temperature
- Cooling by free air convection
- Built-in constant current limiting circuit
- 1U low profile 38mm
- Built-in remote ON-OFF control
- Stand by 5V@0.3A
- Built-in remote sense function
- No load power consumption<0.5W

**Uitgang**

dc spanning : 36V  
Stroom (max.) : 4.3A  
Vermogen : : 155W  
Ripple & Noise (max.) : 200mVp-p  
Spanning instelbaar : 28.8 ~ 39.6V  
IP-classificatie :

Ingang spanning : 85 ~ 264VAC 120 ~ 373VDC  
Frequentie : 47 ~ 63Hz

Dimension : 159x97x38mm

## Productinformatie

---

Artikelnummer	HRPG15036
Merk	MEANWELL
Is on Sale	Nee

