

LED VOEDING 12V/16A 192W IP65 BEHUIZING

€ 99,00

Excl. BTW: € 81,82

Afbeeldingen



Beschrijving

Universal AC input / Full range
Built-in active PFC function
Protections: Short circuit / Over current / Over voltage / Over temperature
Cooling by free air convection
OCP point adjustable through output cable or internal potentiometer
IP67 / IP65 design for indoor or outdoor installations
Type HL LED Driver for use in Class ζ^1 , Division 2 hazardous location luminaires
Three in one dimming function (1~10Vdc or PWM signal or resistance)
Suitable for LED lighting and street lighting applications
Compliance to worldwide safety regulations for lighting
Suitable for dry / damp / wet locations

Uitgang

dc spanning : 12V
Stroom (max.) : 16A
Vermogen : : 192W
Ripple & Noise (max.) : 150mVp-p

Spanning instelbaar : 11.2 ~ 12.8V

IP-classificatie : IP65

Adjustable output voltage with internal potentiometer

Adjustable output current with internal potentiometer

Ingang spanning : 90 ~ 264VAC 127 ~ 373VDC

Frequentie : 47 ~ 63Hz

Productinformatie

Artikelnummer	HLG24012A
Merk	MEANWELL
Is on Sale	Nee

