

GESCHAKELDE VOEDING SINGLE OUTPUT 35W 24V/1.5A

€ 23,50

Excl. BTW: € 19,42

Afbeeldingen



Beschrijving

Universal AC input / Full range
Protections: Short circuit/Over load/Over voltage
Cooling by free air convection
LED indicator for power on
100% full load burn-in test
All using 105
Withstand 300VAC surge input for 5 second
High operating temperature up to 70
Withstand 5G vibration test
High efficiency, long life and high reliability

MODEL RS-35-24

OUTPUT:

DC VOLTAGE 24V

RATED CURRENT 1.5A

CURRENT RANGE 0 ~ 1.5A

RATED POWER 36W

RIPPLE & NOISE (max.) 120mVp-p

OUTPUT VOLTAGE ADJ. RANGE 22 ~ 27.6V

VOLTAGE TOLERANCE +/-1.0%

LINE REGULATION +/-0.5%

LOAD REGULATION +/-0.5%

SETUP, RISE TIME 500ms, 30ms/230VAC

HOLD TIME (Typ.) 80ms/230VAC at full load

INPUT:

VOLTAGE RANGE 88 ~ 264VAC

FREQUENCY RANGE 47 ~ 63Hz

EFFICIENCY(Typ.) 84%

AC CURRENT (Typ.) 0.8A/230VAC

INRUSH CURRENT (Typ.) COLD START 33A/230VAC

LEAKAGE CURRENT <2mA / 240VAC

PROTECTION:

OVER LOAD 110 ~ 150% rated output power

Protection type : Hiccup mode, recovers automatically after fault condition is

OVER VOLTAGE 27.6 ~ 32.4V Protection type : Hiccup mode, recovers automatically after fault condition is removed

Dimensions 99*82*36mm (L*W*H)

Productinformatie

Artikelnummer	RS3524
Merk	MEANWELL
Is on Sale	Nee

